



## LET LOOSE

PRODUCT NUMBER: 5612

A scientifically formulated penetrating oil and rust dissolver containing micron size particles of PTFE and Moly. This super penetrant carries the PTFE and molybdenum disulfide particles into the threads, crevices, etc. These particles act as millions of tiny ball bearings to prevent seizing and galling while the parts are being removed.



### APPLICATIONS

Used on all dismantling jobs throughout the plant, shop or wherever parts are frozen or hard to operate. Quickly loosens corroded nuts, studs, bolts, flanges and pipe joints.

### FEATURES & BENEFITS

- Contains PTFE and Moly for high pressure performance and decreased metal wear
- Clinging formula for improved lubricity and coverage
- Does not contain silicone or chlorinated solvents

### SPECIFICATIONS

**FORM:** Solvent Based Aerosol

**COLOR:** Brown to Amber

**WETTING ABILITY:** Saturates

**COLD STABILITY:** 0°F

**FLASH POINT:** 110°F

**SOLUBILITY IN WATER:** 0.00%

**VOC:** 12%

**EVAPORATION RATE:** Slow

**ODOR:** Petroleum Solvent Odor

**TOXICITY:** 400 ppm OSHA TLV

**STORAGE STABILITY:** 1 Year +

**PHOSPHATES:** None

**FLAME EXTENSION:** 18"

**SPECIFIC GRAVITY:** 0.825

**PROPELLANT:** Hydrocarbon

**BIODEGRADABILITY:** No

[WWW.METALLOIDONE.COM](http://WWW.METALLOIDONE.COM)

1160 WHITE STREET STURGIS, MI 49091