# METSOL 9000 Bio-stable Soluble Oil Machining Coolant



**The Metalloid Partnership Advantage** 

### **Product Description**

METSOL 9000 is a high performance heavy-duty, bio-stable, water soluble coolant for machining and grinding of ferrous and non-ferrous metals. METSOL 9000 is formulated to provide exceptional tool life and long term, trouble free performance with superior tramp oil rejection. The unique chemistry of METSOL 9000 forms a bio-stable emulsion that resists the growth of bacteria, resulting in excellent rancidity control. This exclusive formulation also provides a coolant that is low foaming, making it an excellent choice for high pressure and through spindle coolant spray. METSOL 9000 can be used in individual sumps and central systems.

## **Benefits**

- ✓ Remains stable in sump for longer periods of time
- ✓ Excellent rancidity control
- ✓ Low foaming excellent for high pressure machining
- ✓ Excellent corrosion protection
- ✓ Excellent lubricity and cooling properties
- ✓ Superior tramp oil rejection
- ✓ Bio-stable effective bacterial inhibition

### **Directions For Use**

**METSOL 9000** is diluted in water at concentrations appropriate for the severity of the operation. The machine sump should always be cleaned with METALLOID machine cleaner and rinsed prior to adding fresh coolant.

### **Recommended Starting Solutions:**

Milling, Drilling, Turning	1:10 to 1:20
Reaming, Broaching, Tapping	1:10 to 1:20
Grinding and Sawing	1:20 to 1:30

**Note:** Coolant should always be added to water. Do not add water to concentrate.

Proper dilutions can easily be monitored by refractive index. Refractometers are available through Metalloid Corporation and its distributors.

# **Packaging**

METSOL 9000 is available in 5 gallon pails, 55 gallon drums, 330 gallon totes and bulk quantities.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for loss, damage, or expense, direct or consequential, arising out of their use.

No one understands metalworking fluids better than Metalloid, so no one else can bring you advanced technology that works on the issues that matter to you. Get the whole story by calling

Metalloid at **800.686.3201**.



Michigan Facility
1160 White Street
Sturgis, MI 49091
telephone 269.503.7300
facsimile 269.503.7795

Texas Facility 1720 N. Quevado St. Jacksonville, TX 75766 telephone 903.589.3933 facsimile 903.589.3924

www.metalloidcorp.com/metalworking



PROPERTIES	
Appearance	Clear, amber
	liquid
Odor	Mild
Specific Gravity	0.895
Water Solubility	Completely
pH (5%)	9.3
Refractometer	1.00
Multiplier	