TAPEZE X-3 All Metal Tapping Fluid







Product Description

TAPEZE X-3 is a high viscosity, E.P. fortified tapping and cutting fluid that is safe for all metals. **TAPEZE X-3** is formulated to "*cling*" to your tap or tooling to afford the maximum of lubricity and tap life.

Benefits

- Increased tap life
- Safe on all metals, including aluminum and stainless steel
- Improved part finishes
- Eliminates chipping and galling
- Improved thread quality
- Reduces tool breakage
- "Splits Out" of machining coolants
- "clings" to tool without mess or waste
- Economical can use as is or as an additive

Applications

- Hand tapping
- Blind hole tapping
- CNC tapping
- External broaching
- Heavy-duty forming
- Threading
- Reaming
- Cutting
- Extruding

Directions For Use:

TAPEZE X-3 is used as received. **TAPEZE X-3** can diluted with mineral oil for less severe operations.

The Metalloid Partnership Advantage



Properties

Appearance	Clear amber thick liquid
Odor	Characteristic
Specific Gravity	0.934
Viscosity	1,800 S.U.S. @100 F
Flash Point	375 F. C.O.C.
Odor Specific Gravity Viscosity	Characteristic 0.934 1,800 S.U.S. @100 F

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, expressed or implied, and we assume no responsibility for loss, damage, or expense, direct or consequential, arising out of their use.

No one understands metalworking fluids better than Metalloid, so no one else can bring you advanced technology that works on the issues that matter to you. Get the whole story by calling Metalloid at **800.686.3201**.



Michigan Facility 1160 White Street Sturgis, MI 49091 telephone 269.503.7300 facsimile 269.503.7795 Texas Facility 1720 N. Quevado St Jacksonville, TX 75766 telephone 903.589.3933 facsimile 903.589.3924

www.metalloidcorp.com/metalworking